(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 24 November 2005 (24.11,2005)

PCT

(10) International Publication Number

(51) International Patent Classification7:

B23B

WO 2005/110648 A2

(21) International Application Number:

PCT/IB2005/001276

(22) International Filing Date:

11 May 2005 (11.05.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2004/3618

12 May 2004 (12.05.2004) ZA

(71) Applicant (for all designated States except US): ELE-MENT SIX (PTY) LTD [ZA/ZA]; Debid Road, Nuffield, 1559 Springs (ZA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): ACHILLES, Roy, Derrick [ZA/ZA]; 608 San Martinho, Leicester Road, 2007 Bedfordview (ZA).

(74) Agents: DONALD, Heather, June et al.; Spoor & FisherIP. O. Box 41312IICraighall, 2024 Johannesburg (ZA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC. VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GO, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CUTTING TOOL INSERT



(57) Abstract: A polycrystalline diamond abrasive cutting element consists generally of a layer of high grade polycrystalline diamond bonded to a cemented carbide substrate. The polycrystalline diamond layer has a working surface and an outer peripheral surface and is characterised by having an annular region or a portion thereof adjacent the peripheral surface that is lean in catalysing material. A region adjacent the working surface is also lean in catalysing material such that in use, as a wear scar develops, both the leading edge and the trailing edge thereof are located in a region lean in catalysing material.

WO 2005/110648 A2